



## QSW-M408S

Management Type	Web Managed
Fanless	Yes
Jumbo Frames	9K
Electromagnetic Compliance	CLASS A
Certifications	CE, FCC, VCCI, BSMI
Relative Humidity	5~95% Non-condensing
Operating Temperature	0°C to 45°C (32°F to 113°F)
Weight (Gross)	1.565 kg
Weight (Net)	1.145 kg
Dimensions (HxWxD)	42.5 × 290 × 127 mm
Buttons	Reset button
LED Indicators	Per Port: Speed/Link/Activity Per System: Power/Status
Form Factor	Desktop
Supported Standards	IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-SX/LX IEEE 802.3ae 10G Fiber IEEE 802.3x Full-Duplex Flow Control IEEE 802.1Q VLAN Tagging IEEE 802.1w RSTP IEEE 802.3ad LACP IEEE 802.1AB LLDP IEEE 802.3az Energy Efficient Ethernet IEEE 802.1p Class of Service
Fan	Fanless
Number of Ports	12

Energy Efficient Ethernet (IEEE 802.3az complaint)	Yes
Console (Opt.)	RJ45
Management Interface	Web
Switching Capacity	96Gbps
Total Non-Blocking Throughput	48Gbps
MAC Address Table	16K
Input Voltage Range	100-240VAC, 50/60 Hz
Input Power Type	AC
Max. Power Consumption	12.17 W
Power Supply Description	Adapter
1GbE (RJ45)	8
10GbE SFP+	4
Warranty	2 Years