

Key **Features**

- Intuitive 10-point touchscreen
- Finger, stylus, and glove touch compatible
- Magnetic pen placeholder
- Adjustable back tilt up to 40-degrees
- Scratch-resistant 7H hardness screen



Product **Description**

The ViewSonic® TD2423 is a 24" IR touch display designed for intuitive multi-touch use. Infrared (IR) touchscreen can detect up to 10 points of contact compared to optical touchscreens and can be operated by a stylus, fingers and gloved hands. The multi-touch input is more accurate, and the display is faster. Coupled with an adjustable tilt, you can easily interact with the TD2423 at an ideal position. This monitor features Full HD resolution to give you clear images and is built with scratch-resistant 7H hardness screen to surface damage. To support your work, the TD2423 is equipped with VGA, HDMI, DVI and USB connectivity.



Visit Us www.viewsonic.com

DISPLAY		WALL MOUNT	
Display Size (in.):	24	VESA Compatible:	100 x 100 mm
Viewable Area (in.):	23.6	INPUT SIGNAL	
Panel Type:	VA Technology	Frequency Horizontal:	24 ~ 82KHz
Resolution:	1920 x 1080	Frequency Vertical:	50 ~ 75Hz
Resolution Type:	FHD	VIDEO INPUT	
Static Contrast Ratio:	3,000:1 (typ)	Digital Sync:	TMDS - DVI-D, TMDS - HDMI (v1.4)
Dynamic Contrast Ratio:	20M:1	Analog Sync:	Separate/Composite/SOG - RGB
Light Source:	LED		Analog
Brightness:	250 cd/m² (typ)	ERGONOMICS	
Colors:	16.7M	Tilt (Forward/Back):	22º / 38º
Color Space Support:	8 bit (6 bit + Hi-FRC)	WEIGHT (IMPERIAL)	44.5
Aspect Ratio:	16:9	Net (lbs):	11.5
Response Time (Typical GTG):	7ms	Net Without Stand (lbs):	10.3
Response Time (GTG w/OD):	7ms	Gross (lbs):	15.4
	25ms	WEIGHT (METRIC)	5.0
Response Time (Typical Tr+Tf):		Net (kg):	5.2
Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (kg):	4.7
Backlight Life (Hours):	40000 Hrs (Min)	Gross (kg):	7
Curvature:	Flat	DIMENSIONS (IMPERIAL) (W	·
Refresh Rate (Hz):	75	Packaging (in.):	25.4 x 16.6 x 6.5
Blue Light Filter:	Yes	Physical (in.):	22.5 x 13.7 x 4
Flicker-Free:	Yes	Physical Without Stand (in.):	22.5 x 13.7 x 2.4
Color Gamut:	NTSC: 72% size (Typ), sRGB: 104% size (Typ)	DIMENSIONS (METRIC) (WX	·
Pixel Size:	0.272 mm (H) x 0.272 mm (V)	Packaging (mm):	645 x 422 x 166
Touch Screen:	IR, 10-point multi-touch	Physical (mm):	571 x 348 x 101
Surface Treatment:	Glossy, Hard Coating (7H)	Physical Without Stand (mm):	571 x 348 x 61
Cover Glass Thickness:	1.85mm	GENERAL	
COMPATIBILITY	1.0311111	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico
PC Resolution (max):	1920x1080		Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, PSE, CCC, China RoHS, China
Mac® Resolution (max):	1920x1080		
PC Operating System:	Windows 10 certified; macOS tested		Energy Label, CECP
	1920x1080		TD2423 x1, 3-pin Plug (IEC C13 /
Mac® Resolution (min): CONNECTOR	1920x 1080	PACKAGE CONTENTS:	CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v2.0;
VGA:	1		Male-Male) x1, Audio Cable (Male- Male) x1, Quick Start Guide x1
USB 2.0 Type A:	2	Recycle/Disposal:	Please dispose of in accordance with
USB 2.0 Type B:	1	1 tooy olo, Blop coul.	local, state or federal laws.
3.5mm Audio In:	1	Warranty:	*Warranty offered may differ from market to market
		Power Management:	Energy Star standards, EPEAT
3.5mm Audio Out:	1		
HDMI 1.4:	1		
DVI-D:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO	OW # 0		
Internal Speakers:	2Watts x2		
POWER	44 510		
Eco Mode (Conserve):	11.5W		
Eco Mode (optimized):	13.5W		
Consumption (typical):	15.5W		
Consumption (max):	16.5W		
Voltage:	AC 100-240V, 50/60 Hz		
Stand-by:	0.5W		
Power Supply:	Internal		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	1, 2, Up, Down, Power		
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		

Copyright © ViewSonic Corporation 2000-2020. All rights reserved.

Humidity (non-condensing):

20% to 90%